



NOTE :  
- MARKING 'A' is used to identify "STANDARD" terminal  
- CRIMPING SPECIFICATION ACCORDING TO AS-64322-001

2	BOX TERMINAL	STAINLESS STEEL thickness=0.15 mm
1	BODY TERMINAL	high conductivity copper alloy thickness=0.2 mm
MARK	DESIGNATION	MATERIAL

(SKC) COTES CARACTERISTIQUES SPECIALES  
SPECIAL KEY CHARACTERISTICS  
INDICATION DIMENSIONS S.P.C  
DENOTES S.P.C DIMENSIONS  
INDICATION DIMENSIONS CRITIQUES  
DENOTES CRITICAL DIMENSIONS  
INDICATION DIMENSIONS FONCTIONNELLES  
DENOTES FUNCTIONAL DIMENSIONS  
QUANTITE PAR FEUILLE INDIVIDUELLE  
QUANTITY PER INDIVIDUAL SHEET

1 0 4 (SKC) 0

0643221029	Sn	Sn			0.75	2.5	2.4	0.6	3.3	2.8	0.75	0.119
0643221219	Au 1.27μ MINI	Sn	Ni		0.50	2.3	2.2	0.6	3.1	2.6	0.75	0.117
0643221039	Sn	Sn			0.22 TO 0.44	2.0	1.7	0.6	3.1	2.6	0.75	0.112
0643221239	Au 1.27μ MINI	Sn	Ni									
0643221019	Sn	Sn										
0643221229	Au 1.27μ MINI	Sn	Ni									
PART NUMBER	CONTACT AREA	CRIMPING AREA	UNDERLAYER	CRIMPING RANGE (mm2)	A±0.2	B±0.2	rC +0.15 -0.1	D±0.2	E±0.2	F±0.1	WEIGHT (g)	
	PLATING											

**GENERAL TOLERANCES (UNLESS SPECIFIED)**

4 PLACES ±	---	±	---
3 PLACES ±	---	±	---
2 PLACES ±	0.10	±	---
1 PLACE ±	0.1	±	---
0 PLACE ±	0.1	±	---

ANGULAR ± 2°  
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

**GENERAL TOLERANCES (UNLESS SPECIFIED)**

mm	INCH
4 PLACES ±	---
3 PLACES ±	---
2 PLACES ±	0.10
1 PLACE ±	0.1
0 PLACE ±	0.1

SEE CHART

**UPDATE VIEWS**  
EC NO: DAU2014-060  
DRAWN BY: SMITH  
CHKD BY: HERBEL  
APPR BY: BOSSEL

2013/07/15  
2013/07/31  
2013/08/20

**DESCRIPTION**

**GENERAL TOLERANCES (UNLESS SPECIFIED)**

**DIMENSION STYLE**  
MM ONLY

**SCALE**  
20:1

**DESIGN UNITS**  
METRIC

**FIRST ANGLE PROJECTION**

**TITLE**  
CP RCPT TRM 0.6

**DATE**  
2007/09/17

**CHECKED BY**  
JDUCLOS

**APPROVED BY**  
LSTICKEIR

**DATE**  
2007/09/17

**MATERIAL NO.**

**DOCUMENT NO.**  
SD-64322-001

**SHEET NO.**  
1 OF 1

**INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION**