



RECOMMENDED PC BOARD LAYOUT

- 1 HOUSING MATERIAL: GLASS FILLED POLYESTER, COLOR- BLACK
- 2 CONTACT MATERIAL: PHOSPHOR BRONZE
- 3 CONTACT FINISH: 0.00254[.000100] MIN THK BRIGHT TIN-LEAD, OVER 0.00127[.000050] MIN NICKEL OVER ENTIRE CONTACT
- 4 MOLDED IN ARROW DESIGNATES THE MATING FACE OF THE CONNECTOR
- 5 POINT OF MEASUREMENT FOR PLATING THICKNESS OF CONTACT AREA
- 6 DIMENSIONS PERTAIN TO HOUSING CAVITY CENTERLINES
- 7 MARK PART NUMBER AND DATE CODE IN APPROXIMATE LOCATION SHOWN, EITHER END.
- 8 ALTERNATE LOCATION FOR DATE CODE FOR 2 AND 3 POSITION.
- 9 NO PART NUMBER MARKING REQUIRED FOR THIS PART.
- 11 TE LOGO AND CSA LOGO ARE MOLDED INTO HOUSING, THIS LOCATION

162.56[6.400]	165.10[6.500]	65	6-535677-4	
160.02[6.300]	162.56[6.400]	64	6-535677-3	
157.48[6.200]	160.02[6.300]	63	6-535677-2	
154.94[6.100]	157.48[6.200]	62	6-535677-1	
152.40[6.000]	154.94[6.100]	61	6-535677-0	
149.86[5.900]	152.40[6.000]	60	5-535677-9	
147.32[5.800]	149.86[5.900]	59	5-535677-8	
144.78[5.700]	147.32[5.800]	58	5-535677-7	
142.24[5.600]	144.78[5.700]	57	5-535677-6	
139.70[5.500]	142.24[5.600]	56	5-535677-5	
137.16[5.400]	139.70[5.500]	55	5-535677-4	
134.62[5.300]	137.16[5.400]	54	5-535677-3	
132.08[5.200]	134.62[5.300]	53	5-535677-2	
129.54[5.100]	132.08[5.200]	52	5-535677-1	
127.00[5.000]	129.54[5.100]	51	5-535677-0	
124.46[4.900]	127.00[5.000]	50	4-535677-9	
121.92[4.800]	124.46[4.900]	49	4-535677-8	
119.38[4.700]	121.92[4.800]	48	4-535677-7	
116.84[4.600]	119.38[4.700]	47	4-535677-6	
114.30[4.500]	116.84[4.600]	46	4-535677-5	
111.76[4.400]	114.30[4.500]	45	4-535677-4	
109.22[4.300]	111.76[4.400]	44	4-535677-3	
106.68[4.200]	109.22[4.300]	43	4-535677-2	
104.14[4.100]	106.68[4.200]	42	4-535677-1	
101.16[4.000]	104.14[4.100]	41	4-535677-0	
96.52[3.800]	99.06[3.900]	39	3-535677-9	
93.98[3.700]	96.52[3.800]	38	3-535677-8	
91.44[3.600]	93.98[3.700]	37	3-535677-7	
88.90[3.500]	91.44[3.600]	36	3-535677-6	
86.36[3.400]	88.90[3.500]	35	3-535677-5	
83.82[3.300]	86.36[3.400]	34	3-535677-4	
81.28[3.200]	83.82[3.300]	33	3-535677-3	
78.74[3.100]	81.28[3.200]	32	3-535677-2	
76.20[3.000]	78.74[3.100]	31	3-535677-1	
71.12[2.800]	73.66[2.900]	29	3-535677-0	
68.58[2.700]	71.12[2.800]	28	2-535677-9	
66.04[2.600]	68.58[2.700]	27	2-535677-8	
63.50[2.500]	66.04[2.600]	26	2-535677-7	
60.96[2.400]	63.50[2.500]	25	2-535677-6	
58.42[2.300]	60.96[2.400]	24	2-535677-5	
55.88[2.200]	58.42[2.300]	23	2-535677-4	
50.80[2.000]	53.34[2.100]	21	2-535677-3	
99.06[3.900]	101.16[4.000]	40	2-535677-2	
73.66[2.900]	76.20[3.000]	30	2-535677-1	
48.26[1.900]	50.80[2.000]	20	2-535677-0	
45.72[1.800]	48.26[1.900]	19	1-535677-9	
43.18[1.700]	45.72[1.800]	18	1-535677-8	
40.64[1.600]	43.18[1.700]	17	1-535677-7	
38.10[1.500]	40.64[1.600]	16	1-535677-6	
35.56[1.400]	38.10[1.500]	15	1-535677-5	
33.02[1.300]	35.56[1.400]	14	1-535677-4	
27.94[1.100]	30.48[1.200]	12	1-535677-3	
25.40[1.000]	27.94[1.100]	11	1-535677-2	
22.86[.900]	25.40[1.000]	10	1-535677-1	
20.32[.800]	22.86[.900]	9	1-535677-0	
17.78[.700]	20.32[.800]	8	535677-9	
10.16[.400]	12.70[.500]	5	535677-8	
7.62[.300]	10.16[.400]	4	535677-7	
SUPERSEDED BY 5535677-6	5.08[.200]	7.62[.300]	3	535677-6
2.54[.100]	5.08[.200]	2	535677-5	
53.34[2.100]	55.88[2.200]	22	535677-4	
30.48[1.200]	33.02[1.300]	13	535677-3	
SUPERSEDED BY 5535677-2	15.24[.600]	17.78[.700]	7	535677-2
12.70[.500]	15.24[.600]	6	535677-1	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	0 PLC ± -	1 PLC ± -	2 PLC ± -	3 PLC ± 0.13[.005]	4 PLC ± -	ANGLES ± -
----------------	--	-----------	-----------	-----------	--------------------	-----------	------------

MATERIAL: FINISH:

APPROVED BY: J. OLSON, DATE: 03JUN02

NAME: AMPMODU MOD II RECEPTACLE ASSEMBLY, HORIZONTAL, .100 CL, SINGLE ROW, CLOSED-ENTRY, SHORT POINT OF CONTACT, END-TO-END STACKABLE

SIZE: A1, CAGE CODE: 00779, DRAWING NO: 535677

WEIGHT: -

CUSTOMER DRAWING: SCALE: 5:1, SHEET: 1 OF 1, REV: M4